



CORAL DUO

WALL LIGHT

Designed by Oliver Höglund & Ryan Roberts




TECHNICAL DATA

Application	Interior Use (Optional: Outdoor Use) Low Voltage (under 12v)	Input Power	100-240V AC
Glass	Frosted / Clear	Output Power	8V DC Driver (350mA Constant Current) Supplied with Remote Driver
Wall Mount Finish	Matte Black / Matte White / Brass Finish Steel Finish / Bronze	Dedicated LED	2 x 1W - (Standard) / 2 x 2W (additional cost) Lifespan - 60,000+ Hours CRI>90
Glass Dimensions	150mm Overall measurement 340mm inc glass	Colour Temperature	2700K / 3000K (Standard) / 4000K
	Wall Mount: 230 x 60mm Protrudes: 50mm	Dimming	TRIAC/Phase Dimmable (Standard) DALI (additional cost) Please contact for alternative dimming options
IP Rating	IP20 Indoor	Mounting	Integral Wall Bracket
Warranty	24 Months / 2 Years	Certification	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN ETL/UL 1598, CSA C22.2#250.0

DIMENSIONS


Glass Installation



To install the glass piece, hold the glass against the LED housing and thread the 30mm threaded cap into the LED housing.


*Ensure the rubber o-ring(s) are installed in the correct position. If the glass is not held firmly when the threaded cap is fully screwed in, install the second o-ring behind the glass.

Wall Plate Dimensions




MOUNTING

Installation Instructions




1. Unscrew the grub screw to separate the screw plate from the face plate.

Prep the wall with a hole to match the cutout in the screw plate.



2. Install the screw plate to the wall using appropriate fasteners for the wall substrate. Secure the transformer into the wall cavity and feed the cable through the hole into the room. Connect the single electrified cable to the transformer.

*The transformer needs to be accessible for maintenance purposes.



3. Fit the wall plate over the mounting plate and secure with the supplied M4 grub screw at the top of the plate.