SØKTAS

CORAL TRI ROD

PENDANT LIGHT

Designed by Oliver Höglund & Ryan Roberts




TECHNICAL DATA

Application	Interior & Outdoor Use
Glass	Frosted / Clear
Rod Finish	Matte Black / Matte White / Brass Finish Steel Finish / Bronze Finish
Glass Dimensions	3 x 120mm
IP Rating	IP44
Warranty	36 Months / 3 Years
Certification	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN ETL/UL 1598, CSA C22.2#250.0

Input Power	100-240V AC
Output Power	12V DC Driver (350mA Constant Current) Supplied with Remote Driver
Dedicated LED	3 x 1W (Standard) / 3 x 2W Lifespan - 100,000+ Hours CRI>90
Colour Temperature	2700K / 3000K (Standard) / 4000K
Dimming	TRIAC/Phase Dimmable (Standard) DALI (additional cost) Please contact for alternative dimming options


DIMENSIONS


Glass Installation



To install the glass piece, hold the glass against the LED housing and thread the 30mm threaded cap into the LED housing.


*Ensure the rubber o-rings are installed in the correct position, 1 behind the glass, and 1 in-front on the glass. If the glass is not held firmly when the threaded cap is fully screwed in, install an extra o-ring.






MOUNTING

Installation Instructions




Prep the ceiling with an approx. 50mm hole to fit the transformer. Place the transformer in the ceiling and feed the cable through the hole into the room. Connect the single electrified cable to the transformer.

*The transformer needs to be accessible for maintenance purposes.



Screw the steel mounting plate to the ceiling using appropriate fasteners for the ceiling substrate.



Secure the magnetic cover plate onto the mounting plate.