



SONN WALL LIGHT

Designed and Handmade by Oliver Höglund & Ryan Roberts

Illuminate your space with the Sonn wall light, a petite and elegant clear glass-blown fixture perfect for enhancing bathrooms, hallways, and kitchen areas. Created as an adaptation of the Sora wall light, its distinctive half-sphere design renders it a captivating focal point that exudes elegance from every perspective. Tailor it to your preferences by selecting a wall plate finish of brass finish, matte black, matte white, medium bronze or steel finish and set the mood of your space with a choice of warm, warm white, or white LED temperatures. Meticulously hand-blown using premium Swedish clear glass, each piece carries the distinctiveness of SOKTAS Glass designs, promising an unparalleled and personalised lighting masterpiece that adds both elegance and character to your space.

Hand-Blown in Currumbin, Australia



TECHNICAL DATA

Application Interior & Outdoor Use

Glass Clear

Wall Plate Finish Matte Black / Matte White / Brass Finish /

Steel Finish / Medium Bronze Powdercoat

Dimensions Glass: 100 - 120mm

Mounting Plate: 110 x 20mm

Protudes: 80 - 100mm

Weight 0.5kg

IP Rating IP55

Warranty 24 Months / 2 Years

Certification AU/NZ AS/NZS 60598.1, 60598.2.1

EU EN 60598.1, 60598.2.1

US/CAN ETL/UL 1598, CSA C22.2#250.0

Input Power 100-240V AC

Output Power 4V DC Driver (350mA Constant Current)

Supplied with Remote Driver

Dedicated LED 1W - 350mA (Standard) / 2W (additional cost)

Lifespan - 60,000+ Hours

CRI>90

Lumen Output 150lm (1W) (Standard) / 300lm (2W)


Colour Temperature 2700K / 3000K (Standard) / 4000K


Dimming Triac-Dimmable (Standard)

Optional: DALI (additional cost)
Please contact for alternative dimming options

Mounting Integral Wall Bracket


DIMENSIONS





MOUNTING

Installation Instructions



screw plate from the circular face plate.


Prep the wall with a hole to match the cutout in the screw plate.



Install the screw plate to the wall using appropriate fasteners for the wall substrate.

Secure the transformer into the wall cavity and feed the cable through the hole into the room. Connect the single electrified cable to the transformer.

*The transformer needs to be



Fit the circular wall plate over the mou plate and secure with the supplied Ma screw at the top of the plate.