



SORAPENDANT

Designed and Handmade by Oliver Höglund & Ryan Roberts

Featuring an enchanting hand-blown glass shade, the Sora pendant light offers a selection between clear or captivating bubble glass finishes, resulting in a stunning soft illumination that establishes an ideal centerpiece either individually or in clusters above stairwells, dining tables, and within bathrooms. The bubble glass finish casts a distinctive shadow pattern along your space's walls, introducing a captivating burst of champagne-like effervescence. Suspended gracefully by a steel cable, it attaches through a sleek lampholder available in finishes of as brass finish, matte black, medium bronze, or steel finish. Choose between warm, warm white, or white LED temperatures to set your desired ambiance. Meticulously hand-blown using premium Swedish clear glass, each glass shade carries the distinctiveness of SOKTAS Glass designs, promising an unparalleled and personalised lighting masterpiece that adds both elegance and character to your space.

Hand-Blown in Currumbin, Australia.



TECHNICAL DATA

Application Interior Use Only

Low Voltage (under 12v)

Glass Colour Clear

Lampholder Finish Matte Black / Brass Finish / Steel Finish /

Matte White / Medium Bronze Powdercoat

Ceiling Mount Matte Black / Matte White

Dimensions 100 x 100mm (approx.)

Suspension 1500mm Steel / Black / White Cable

Longer lengths on request

Weight 0.5kg

Warranty 24 Months / 2 Years

Certification CE / AS/NZS - 60598.2.1

Input Power 100 - 240V AC

Output Voltage 4V DC Driver (350mA Constant Current)

Supplied with Remote Driver

Dedicated LED 1W - 350mA (Standard) / 2W (additional cost)

Lifespan - 60,000+ Hours

CRI>90

Lumen Output 150lm (1W) (Standard) / 300lm (2W)

Colour Temperature 2700K / 3000K (Standard) / 4000K

Dimming Single-Use-1W LED Non-Dimmable (Standard)


Optional: Single-use - 2W LED Triac Dimmable DALI Dimmable (additional cost)

Please contact for alternative dimming options

Mounting 81mm Flat disc recessed ceiling plate

Custom designed ceiling plate on request

DIMENSIONS





MOUNTING

stallation instructions

1 2 3

Prepare ceiling with a 60mm diameter hole. Plate size: ø81 x 3mm

Connect the single electrified cable to the driver.



Flip up springs and fit through 60mm hole. Release springs to secure plate around ceiling substrate. (Maximum weight loading 1kc

*Push up the metal cable gripper on the mounting plate to adjust the cable lengt